

User Manual Car Charger FCC10 TLL151291



Technical Specifications • Input: DC 12-24V • Total output: 6A

 Total power: 38W USB-A Output (QC 3.0): 3.6-6.5V/3A,

6.5-9V/2A. 9-12V/1.5A (18W max) USB-C Output (PD3.0): 5V3A, 9V/2.22A,

12V/1.67A [20W max] • Suported fast charge protocols (USB-C): PPS(3.3-11V/2A)/APPLE 2.4A/DCP 1.5A/QC

2.0/QC 3.0/ AFC/Huawei FCP • Safety protections: Short circuit, overcurrent, overvoltage and overheating • Weight: 23a

Instructions

Material · PC

1. Plug the car charger into your car cigarette liahter. 2. Connect one end of your charging cable to

your device's charging port. 3. Connect the other end to a USB/Type-C port on the car charger.

4. Unplug your device when fully charged.

Caution NOT waterproof; please keep

away from liquid and extreme heat.

• It is normal that the car charger may get a little warm during charging.

Disposal and recycling information

The crossed-out wheeled-bin symbol on your product, battery, literature or packaging reminds you that all electronic products and batteries must be taken to separate waste collection points at the end of their working lives; they must not be disposed of in the normal waste stream with household garbage.

It is the responsibility of the user to dispose of the equipment using a designated collection point or service for separate recycling of waste electrical and electronic equipment (WEEE) and batteries according to local laws.

Proper collection and recycling of your equipment helps ensure EEE waste is recycled in a manner that conserves valuable materials and protects human health and the environment, improper handling, accidental breakage, damage, and/or improper recycling at the end of its life may be harmful for health and environment.