



User Manual Model: TLL151081  25W 3 Ports QC 3.0 CHARGER	1. Product Overview 1.1 Introduction 1.2 Accessories 2. Appearance Description 2.1 Technical Parameters 2.2 Protection 2.3 Material 2.4 Appearance and Interface 3. Operation Instructions Thank you for choosing QC 3.0 Charger. Please read carefully our User Manual before using it, if you have any probelm when using, please contact our customer service, we'll solve it as soon as possible. Any suggestion is welcomed.	1.Product Overview 1.1 Introduction ◆Qualcomm® quick charge 3.0 charger ◆25W (3.6V-6.5V)dc/ 3A, (6.5V-9V)dc/2A, (9V-12V)dc/1.5A Qualcomm® quick charge3.0 technology: Up to 4X faster than standard chargers, able to charge compatible devices to 80%in just 35 minutes, using the USB port with QC 3.0 technology and compatible cable, the voltage flexible change from 3.6V to 12V. ◆Backwards compatible with all versions of Qualcomm Quick Charge technology (1.0, 2.0 & 3.0). ◆Provides standard charging for non-Quick Charge devices. ◆Full speed charging 3 devices at the same time ◆Efficient synchronous rectification scheme, up to 87% of the conversion rate. ◆Elegant, durable, heat eliminable. ◆Over-load, over-voltage, over-current and short circuit protection. ◆Compact and unique appearance design by our own, without any gap. ◆Guaranteed Safety: Premium materials and built-in fail-safes keep you and your device protected against shorts and surges. ◆With 3 pcs Smart IC. 1.2 Accessories ◆25W 3 ports USB CHARGER ◆User Manual 2. Appearance Description 2.1 Technical Parameters ◆Input Voltage: AC 100-240V ◆Quiescent Current: < 300mW ◆QC 3.0 Output: (3.6V-6.5V)/ 3A, (6.5V-9V)/2A, (9V-12V)/1.5A ◆Output port 2: max 2.4A with smart IC ◆Output port 3: max 2.4A with smart IC ◆Max Output Current: 5V/5000mA ◆Max Power: 25W ◆Highest Efficiency: 87% 2.2 Protection ◆Output Short Circuit Protect: To avoid continuing charging devices automatically, on short circuit protection situation, our item will stop charging to protect devices ◆Over Voltage Protection: If Voltage ≧6.2V, protection system will be started ◆High Temperature of main components is higher than 125 C (housing temperature ≧58 C), protection system will be started. If temperature of main components less than 60 C , it will resume working.
---	---	--

Manual de utilizare Model: TLL151081  25W Incarcator Retea - 3 porturi USB	1. Prezentare produs 1.1 Introducere 1.2 Accesorii 2. Descriere 2.1 Parametri tehnici 2.2 Protectie 2.3 Material 2.4 Aspect si interfata 3. Instructiuni Va multumim pentru ca ati ales incarcatorul nostru. Va rugam sa cititi cu atentie manualul de utilizare inainte de folosirea produsului. Daca exista probleme de functionalitate, va rugam sa ne contactati. Orice sugestie este binevenita.	1. Prezentare produs 1.1 Introducere ◆Incarcator 25W Qualcomm quick charge 3.0 ◆Tehnologie: 25W (3.6V-6.5V)dc/ 3A, (6.5V-9V)dc/2A, (9V-12V)dc/1.5A Qualcomm quick charge 3.0: De pana la 4 ori mai rapid, decat incarcatoarele standard, tehnologia Qualcomm quick charge 3.0 inseamna posibilitatea de a incarca dispozitivele compatibile, pana la 80% in doar 35 minute, folosind portul USB cu tehnologie QC 3.0 si cablu compatibil. ◆Compatibil cu toate versiunile tehnologiei Qualcomm Quick Charge (1.0, 2.0, 3.0) ◆Compatibil si cu alte dispozitive non-Quick Charge (incarcare standard) ◆Poate incarca pana la 3 dispozitive, simultan ◆Rata de conversie de pana la 86% ◆Elegant, durabil. ◆Protectie impotriva supraincalzirii , fluctuatiilor de curent si suprasarcinii. ◆Compact, cu un design unic. ◆Materialele premium folosite si functiile avansate de siguranta incorporate va protejeaza pe dumneavoastra si dispozitivul dumneavoastra de cazuri de scurt circuit si supratensiune. ◆3 porturi Smart IC. 1.2 Accesorii ◆Incarcator, 25W, 3 porturi. ◆Manual de utilizare 2. Descriere 2.1 Parametri tehnici ◆Voltaj intrare: AC 100-240V ◆Curent static: < 300mW ◆Iesire port QC 3.0: (3.6V-6.5V)/ 3A, (6.5V-9V)/2A, (9V-12V)/1.5A ◆Iesire port 2: max 2.4A cu iesire inteligenta IC ◆Iesire port 3: max 2.4A cu iesire inteligenta IC ◆Curent maxim iesire: 5V/5000mA ◆Putere maxima: 25W ◆Eficienta maxima: 87% 2.2. Protectie ◆Protectie scurt-circuit (iesire): In situatia in care are loc un scurt circuit, pentru a salva dispozitivele dumneavoastra, incarcatorul va inceta incarcarea pana cand va fi reconectat. ◆Protectie suprasarcina: Daca voltajul creste ≧ 6.2V, sistemul de protectie va porni. ◆In situatia in care componentele principale depasesc temperatura de 120˚C, sistemul de protectie va porni, situatie in care incarcarea va fi reluata odata cu scaderea temperaturii componentelor sub 60˚C.
---	---	---