

## Smart Wi-Fi Ambient Thermostat TLL311431



## Smart temperature in your house











Works with















Technical specs	
Utilization:	Boiler and electric heating systems
Brand compatibility:	Universal
Receiver:	Wired, wall mounted
Receiver connectivity:	Wired to heating system, AC 100-240V 50/60Hz
	Wireless 433MHz (FSK) with central unit (up to 200 meters)
Receiver input load:	Max 3A for boiler, Max 16A for electric heating
Receiver power consumption:	Max 1W
Central unit:	Wall mounted or portable, with display
Central unit connectivity:  Central unit power supply:	Wireless 433MHz (FSK) with receiver (up to 200 meters)
	Wireless 2.4GHz with router
	Wired with Type-C (cable included)
	2 x 1.5V AA batteries (not included)
Display:	2.8" illuminated
Hysteresis:	0.5° C
Temperature measurement accuracy:	0.1° C
Temperature calibration:	Yes, by APP and advanced settings
Temperature statistics:	Yes, by APP
Weekly programing:	Yes, up to 6 periods each day
Frost protection:	Yes, initial status OFF
Child lock:	Yes
Display parameters:	Current temperature, set temperature, clock, current program, outdoor humidity, weather indicator
APP name:	Tellur Smart
Amazon Alexa:	Yes, compatible
Google Assistant:	Yes, compatible
Siri Shorcuts:	Yes, compatible
Wireless frequency:	2.4GHz
WiFi standard:	EEE 802.11b/g/n
Security:	WPA-PSK/ WPA2-PSK /WPA/WPA2/WEP
Encryption type:	WEP/TKIP/AES
Compatibility:	Devices with Android 6 / iOS 11 or higher
Color:	Black
Package includes:	1x Receiver 1x Central unit 1x Type-C cable 1 meter 2x pack of screws
Product dimensions:	Receiver: 86 x 86 x 26mm Central unit: 86 x 118 x 24mm
Product weight:	238gr
Package dimensions:	136 x 98 x 68mm
Package weight:	360gr
Product code:	TLL331431
EAN:	5949120004497



